

Product Datasheet

Product ID: TP-ADAPTOR-R5AC-PTP



TwistPort™ Adaptor for Rocket AC

ADAPTOR FOR ROCKET™ 5AC-PTP OR PTMP

The TwistPort™ Adaptor for Rocket 5AC-PTP and PTMP makes the Rocket™ compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick locking waveguide port. Connecting and disconnecting the Rocket™ 5AC-PTP or PTMP into the TwistPort™ Adaptor is very simple and requires no tools.



TECHNICAL DATA

Antenna Connection	TwistPort™ - Quick Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.4 Kg / 0.9 lbs – single unit 0.5 Kg / 1.1 lbs – single unit incl. package 10.2 Kg / 22.5 lbs – carton (20 units)
Single Unit	Retail Box: 13.5 x 11.5 x 13 cm
20 Units	Carton Box: 28.5 x 28 x 61 cm

PERFORMANCE

Frequency Range	5400 - 5900 MHz
Polarization	Dual Linear H + V
Cross Pol Isolation (Min)	29 dB
VSWR Max	1.8
VSWR Typical	1.4
Impedance 50 Ohm	50 Ohm
Isolation Between Ports	37 dB

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any Symmetrical Horn TP Antenna, any UltraDish™ TP Antenna
Ubiquiti Networks™	Rocket™ 5AC-PTP, Rocket™ 5AC-PTMP

PACKAGE CONTENTS

TwistPort™ Adaptor

PRODUCT DIMENSIONS

