

Product Datasheet

Product ID: TP-ADAPTOR-EPMP



TwistPort™ Adaptor for ePMP 1000

ADAPTOR FOR EPMP™ 1000 AP OR CSM

The TwistPort Adaptor for ePMP™ 1000 AP and CSM makes the ePMP™1000 series compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick-locking waveguide port. Connecting and disconnecting the ePMP™ 1000 AP or CSM into the TwistPort™ Adaptor is very simple and requires no tools.



TECHNICAL DATA

Antenna Connection	TwistPort™ - Quick Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.4 Kg / 0.9 lbs – single unit 0.6 Kg / 1.3 lbs – single unit incl. package 11 Kg / 24 lbs – carton (20 units)
Single Unit	Retail Box: 13 x 12 x 13.5 cm
20 Units	Carton Box: 29 x 28.5 x 60.5 cm

PERFORMANCE

Frequency Range	5400 - 5900 MHz
Polarization	Dual Linear H + V
Cross Pol Isolation (Min)	29 dB
VSWR Max	1.8
VSWR Typical	1.4
Impedance 50 Ohm	50 Ohm
Isolation Between Ports	37 dB

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any Symmetrical Horn TP Antenna, any UltraDish™ TP Antenna
Cambium Networks™	ePMP™ 1000 AP, ePMP™ 1000 CSM

PACKAGE CONTENTS

TwistPort™ Adaptor

PRODUCT DIMENSIONS

