

TwistPort™ Shielded Adaptor for RouterBoard

ADAPTOR FOR RB 9XX, 7XX, 4XX SERIES BOARDS

The TwistPort Shielded Adaptor for RouterBoards make RouterBoard™ 9 series, 7 series and 4 series compatible with all TwistPort™ Antennas. TwistPort Shielded Adaptors are equipped with an integrated shield to decrease RF noise and improve weather resistance.

TwistPort™ Adaptors are equipped with our original quick locking waveguide port. Installing compatible RouterBoards in our TwistPort™ Adaptor is very simple and requires no tools.



TECHNICAL DATA

Antenna Connection	TwistPort™ - Quick Locking Waveguide Port
Radio Connection	2x Right Angle MMCX
Materials	Insert - Aluminium Alloy Shield - Aluminium Body - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h
Weight	0.5 Kg / 1.1 lbs – single unit 0.6 Kg / 1.3 lbs – single unit incl. package 13.8 Kg / 30.4 lbs – carton (20 units)
Single Unit	Retail Box: 21.3 × 15.3 × 9 cm
20 Units	Carton Box: 49 × 33 × 46 cm

PERFORMANCE

Frequency Range	5400 - 5900 MHz
Polarization	Dual Linear H + V
Cross Pol Isolation (Min)	29 dB
VSWR Max	1.8
VSWR Typical	1.4
Impedance 50 Ohm	50 Ohm
Isolation Between Ports	37 dB

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any Symmetrical Horn TP Antenna, any UltraDish™ TP Antenna
MikroTik™	RouterBoard™ RB91x, RB92x, RB71x, RB411L, RB411GL

PACKAGE CONTENTS

TwistPort™ Adaptor RB Body
TwistPort™ Adaptor RB Sticker A
TwistPort™ Adaptor RB Sticker B
Screw 2,9 x 6,5 mm (4 pcs)

PRODUCT DIMENSIONS

